Belinea

[Belinea 10 17 10]

The ideal partner for multimedia application.

The Belinea 10 17 10's new generation screen is now even faster, and a 13 ms response time means watching video is now a real pleasure.

Excellent contrast and brightness levels ensure perfect performance. Along with the integrated speakers, this display is now optimally suited to multimedia use. TCO 99 and ISO 13406-2 certification are proof of the high quality of this display and its optimum ergonomics.

Integrated speaker

D-Sub connection for analogue graphics cards

Belinea 10 17 10 – Faster 17 inch display

- 17 inch (43.18 cm)
- analogue
- Sound, TN-Panel
- Viewing angle: 150° / 135°
- Response time rise / fall: 3 / 10 ms

Target Groups

- **Small and Medium Business**
- **Price sensitive user**
- **Short reponse time for video applications**

MAXDATA Computer GmbH & Co. KG • Elbestraße 12-16 • D-45768 Marl • www.maxdata.de

09/2004 ® Erros and omissions exempt.

MAXDATA
REAL HARD WARE

Belinea 10 17 10 – Technical Data

Panel characteristics

Image size	17"
Viewable image size in inch / cm	17" / 43.18
Max. picture size (w x h) in mm	338 x 270
Physical resolution	1280 x 1024
Pixel pitch in mm	0.264 x 0.264
Active Matrix, TFT	•
Displayable colours (max.)	16.2 Mio (FRC)
Brightness in cd / qm	300
Contrast ratio	500:1
Viewing angle horizontal	150°
Viewing angle vertikal	135°
Coating	Anti Glare
Responsetime: rise / fall in ms	3 / 10
Panel technology	TN
Back Light	4 CCFLs

Electronic data

Horizontal frequency in kHz	31 - 80
Vertical frequency in Hz	56 - 75
Bandwidth in MHz	135
Input voltage 110-230V, 50-60 Hz	•
Power consumption in Watt (On / Sleep)	45 / 1
Input signal (VGA-card) analog / digital	• / –
Output audio amplifier	2 x 2 Watt

Features

Factory / user defined modes	10 / 14
OSD	•
Integrated microphone	–
Integrated speaker	•
Power supply in the panel / in the stand / external	• / – / –
Tilt back / forth	20° / 3°
Swivel right / left	– / –
Color	ClassicGrey

Controls

Brightness / contrast	• / •
H / V position	• / •
Automatic picture-adjustment / colour calibration	• / •
Temperatur	•
Fine adjustment horizontal (clock) / vertical (phase)	• / •
Display at lower resolutions: 1:1 / full screen	– / •
Zoom / frequency	– / •
Recall / video signal selection	• / –
OSD position / OSD language(s)	• / 11
Mute	•
Volume	•

Max. refresh rates in Hz with resolution

640 x 480	75
800 x 600	75
1024 x 768	75
1152 x 864	75
1280 x 1024	75

Approvals / Standards

Plug & Play, DDC1 / 2B	•
Power-Management:	
Energy Star / Energy Label	• / •
TCO99	•
TÜV GS / TÜV Ergonomie	• / •
DIN 29241 / ISO 9241-3, -7, -8 / ISO 13406-2	• / • / •
Compliant to mountings acc.to VESA standard	–
MAC compliant	•

Connections

15-pin Mini-D-Sub	•
24-pin DVI-D	–
Headphone plug	•
Audio In	•

Accessories

User manual (languages)	10
Power cable	•
Video connect. 15-pin Mini-D-Sub	•
Video connect. 24-pin DVI-D	–
Audio cable	•
Microphone cable	–
Pivot software (optional)	–

Physical specification

Size (w x h x d) in mm	373 x 398 x 201
Net / gross weight in kg	3.8 / 5.2

Warranty

3 years incl. Panel and Backlight	•

Austria
MAXDATA Computer GmbH
Ignaz-Köck-Straße 9 • 1210 Wien

Benelux
MAXDATA Benelux B.V.
Bredaseweg 113-115 • 4872 LA Etten-Leur

España • Portugal
MAXDATA Iberia
Edificio Prisma • C/ Colquide, 6
28230 – Las Rozas (Madrid)

France
MAXDATA S.A.R.L.
1, rue de Gevaudan • SILIC 1726
91017 EVRY-LISSES

Germany
MAXDATA Computer GmbH & Co. KG
Elbestraße 12-16 • 45768 Marl

Italy
MAXDATA Italia S.r.l.
Strada 1 • Palazzo F1
I-20090 Milanofiori, Assago (MI)

Poland
MAXDATA Sp. z o.o.
Ursynów Business Park • Ul. Puławska 303
02-785 Warszawa

Switzerland
MAXDATA Computer AG
Haldenstrasse 5 • 6340 Baar

United Kingdom
MAXDATA UK Limited
The MAXDATA Centre • Downmill Road
Bracknell, Berkshire RG12 1QS

With compliments: